

Hunting Mud Motor Specifications

TOOL SIZE (INCHES)	RPM FACTOR (REV/GAL)	FLOW (GPM)	SPEED (RPM)	OPERATING TORQUE (FT-LBS)	STALL TORQUE (FT-LBS)	MAXIMUM W.O.B. (LBS)	LOBES
3 3/4	1.50	80-160	120 - 240	765	800	20,000	4/5
3 3/4	0.82	80-170	65-140	1,800	3,600	20,000	7/8
5	0.56	150-250	80-140	2,500	5,000	36,000	7/8 EXT
5 1/2	0.96	100-250	95-240	1,100	1,500	36,000	4/5
5 1/2	1.00	100-250	100-250	2,000	2,500	36,000	4/5 EXT
5.5 SWB	0.86	80-160	70-135	1,100	2,000	36,000	7/8 2.3X3 3/4
5.5 SWB	0.82	80-170	65-140	1,800	3,600	36,000	7/8 2.3X3 3/4
6 1/4	0.16	200-500	30-80	7,900	11,700	67,000	7/8 ESX
6 3/4	0.38	200-600	75-230	5,250	6,000	67,000	4/5 EXT
6 3/4	0.29	300-600	85-175	5,000	7,500	67,000	6/7 EXT
6 3/4	0.15	200-500	30-77	6,200	7,000	67,000	7/8 ADM
6 3/4	0.29	300-600	85-175	5,200	7,350	67,000	7/8 EXT
6 3/4	0.13	250-450	33-60	7,900	11,700	67,000	7/8 ESX
6 3/4	0.41	200-400	80-165	4,000	5,400	67,000	8/9
6 3/4	0.28	250-650	70-185	3,250	6,700	67,000	9/10
6 3/4	0.28	250-650	70-185	9,000	13,400	67,000	9/10 EXT
6 3/4	0.30	200-600	60-180	12,000	18,300	67,000	9/10 SUP
8	0.11	300-600	33-67	11,050	22,100	88,000	9/10 ESX
8	0.25	600-900	149-223	10,200	20,400	88,000	5/6
9 1/2	0.10	550-1100	55-110	21,000	42,000	110,000	9/10 SUP

COPYRIGHT HUNTING INTERNATIONAL 2002